


# Technical data sheet

## MMS-plus P round head tie, with panhead

Item no. 3498103



Bolt tie for direct mounting without additional anchors in cracked and uncracked concrete and masonry. With round head for universal fastenings. Torx drive T30.  
Construction product tested according to EAD and CE mark, with European Technical Assessment (ETA) and proof of suitability. Load-bearing capacities under fire loads proven up to fire resistance class R120.

#### Substrate

The screw ties are suitable for screwing into the following types of masonry:

- Calcareous sandstone - Full brick (KSV)
- Calcareous sandstone - Hollow brick (KSL)
- Whole brick (Vz)




**St** Steel

**G** Electrogalvanised

### Master data

Item no.	3498103
Type	MMS+ P 6x35
Description 1	Screw anchor
Description 2	with panhead
Dimension	6x35mm
Material description	Steel
Material	Steel
Material symbol	St
Interface description	Electrogalvanised
Surface	Electrogalvanised
Surface to DIN	EN ISO 19598 / EN ISO 4042
Surface symbol	G
Smallest sales unit (VG)	100 Piece
Weight	0,90 kg/100 pc.

### Technical data



Length	35,00 mm
Dimension L	35,00 mm
Dimension	6 x 35 mm
Anchor/nail/bolt version	Spiral anchor
Drill hole diameter	5,00 mm
Anchor length	35,00 mm
Head diameter	11,20 mm
Head shape	Other
Head shape	Other
Thread	6
Screw system	Torx
Screw system	Torx