

Technical data sheet

Injection mortar in cartridge, 420 ml

Item no. 3497803



Styrene-free, vinyl ester composite mortar for spread-free anchoring of high loads with threaded anchor rods. Coaxial cartridge, including one mixing tube, to be worked with the pressing gun, type VM-P 380 Profi.

European Technical Assessment for cracked and uncracked concrete, as well as for masonry of full and hollow brick. Earthquake-proof in concrete according to Category C1. Fire protection approval for concrete and masonry with fire resistance classes up to 120 minutes.

Substrate temperature during processing $-10\text{ }^{\circ}\text{C}$ to $+40\text{ }^{\circ}\text{C}$ (concrete), ambient temperature after complete hardening $-40\text{ }^{\circ}\text{C}$ to $+120\text{ }^{\circ}\text{C}$ (in concrete). If stored in a dark, cool and dry place, will keep for at least 18 months.

Master data

Item no.	3497803
Type	VMU plus 420
Description 1	Injection mortar
Description 2	in cartridge
Dimension	420ml
Smallest sales unit (VG)	1 Piece
Weight	83,00 kg/100 pc.

Technical data

Adhesive application	Construction/mounting
Hardening method	2-component
Contents	420,00 ml
With brush	<input type="checkbox"/>
Delivery form	Cartridge
Transparent	<input type="checkbox"/>