

Technical data sheet

Universal clamp for PV module mounting

Item number: 5901010



Universal clamp to mount photovoltaic modules on flat and pitched roofs, suitable as a clamp between 2 modules or as an end clamp. Lockable pre-fastening on TP 45 support profile and on STK and STL supports. Suitable for 10 mm slot width. Can be rotated through 90° after engaging. Lockable fastening of the PV module with Torx 30 wrench.



- A2

Stainless steel
- BK

Bright

| Master data | |
|------------------------------------|-------------------------------|
| Item number | 5901010 |
| Type | KLU A2 |
| Description 1 | Universal clamp |
| Description 2 | for flat/pitched roof systems |
| Manufacturer | OBO |
| Dimension | 41x42x79 |
| Colour | stainless steel |
| Material | Stainless steel |
| Surface | Bright |
| Surface standard | |
| Smallest sales unit | 20 |
| Unit of quantity | Piece |
| Weight | 6.59 kg |
| Weight unit | kg/100 pc. |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,6786 kg CO2e / 1 Piece |


Technical data sheet

Universal clamp for PV module mounting

Item number: 5901010



Dimensions



| | |
|--------|-------|
| Width | 43 mm |
| Height | 79 mm |

Technical data

| | |
|---|-----------------|
| With fastening material | no |
| Depth | 42 mm |
| Adjustable | yes |
| Photovoltaic connection and fastening element version | Universal clamp |
| For frame height min. | 30 mm |
| For frame height max. | 50 mm |
| Torsion spring stiffness (k.rot.y) | 0 |
| Torsion spring stiffness (k.rot.z) | 0 |
| With module earthing | no |