

Technical data sheet

Trunking unit, blank, height 40–140 mm

Item number: 7424002



Ready-to-mount trunking unit for cable routing consisting of 3 blind lids, 2 side profiles with attached flexible side wall made of metal mesh, floor covering contact profiles with a height H of 3 mm. The scope of supply contains six height-adjustable fastening brackets, six screed anchors and three lid butt seals for nominal trunking widths 200, 300 and 400 mm or six lid butt supports for trunking widths 500 and 600. The essential levelling units (observe height adjustment) for the 400, 500 and 600 lid supports are not contained in the scope of delivery and should be ordered separately. On delivery, the trunking lids are screwed on.




St Steel

FS Strip galvanized

Master data

| | |
|---------------------|--------------------------|
| Item number | 7424002 |
| Type | OKA-G30040140 |
| Description 1 | Flushfloor trunking unit |
| Description 2 | blank |
| Manufacturer | OBO |
| Dimension | 2400x300x140 |
| Material | Steel |
| Surface | Strip galvanized |
| Surface standard | DIN EN 10346 |
| Smallest sales unit | 2.4 |
| Unit of quantity | Metre |
| Weight | 1171.7 kg |
| Weight unit | kg/100 m |

Dimensions



| | |
|--------|----------|
| Length | 2,400 mm |
| Width | 300 mm |

Technical data sheet

Trunking unit, blank, height 40–140 mm

Item number: 7424002



Technical data

| | |
|--|---------|
| Mounting opening cover | no |
| Covers | 3 |
| Mounting system fastening type | Floor |
| Floor plate | no |
| Cover fastening, locking | no |
| Seal installation option | yes |
| Installation opening for on-floor tank | no |
| Decouplable | yes |
| Suitable for expansion joint | no |
| Mesh wall | yes |
| Trunking height, max. | 140 mm |
| Duct height, min. | 40 mm |
| Cover material thickness | 4 |
| Minimum screed height | 40 |
| With connection opening | no |
| With equipotential bonding | no |
| With separating retainer | no |
| With overhang | yes |
| Mounting opening | Without |
| Height-adjustment range, max. | 140 mm |
| Height-adjustment range, min. | 40 mm |
| Removable cover | yes |