Technical data sheet

Extension unit for GES6, height 60-110 mm

Item number: 7424902





Ready-to-mount trunking extension unit with a device installation lid for the instal-lation of a flush-mount unit of nominal size 6, consisting of the trunking base (floor trough with side and floor covering contact profiles), trunking lid with blank mounting opening and a flushfloor end cover. The scope of delivery contains 3 height-adjustable fixing brackets, 3 screed anchors, 1 lid butt support and 1 construction set for 90° angle. Size of the mounting unit suitable for the installation of a rectangular installation

unit of nominal size 6.



Strip galvanized FS

Master data

Item number	7424902
Туре	OKA-W A 6050 6
Description 1	Extension unit
Description 2	for OKA-W
Manufacturer	OBO
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	1
Unit of quantity	Piece
Weight	922 kg
Weight unit	kg/100 pc.

Technical data sheet

Extension unit for GES6, height 60-110 mm

Item number: 7424902

Dimensions



А **新新** т 4 000 000 000 473 6 DB p 000 000 а 400 アマダ 110 60 4Bage 000 000 ß 000 000 473 201 6 000 000

Length	473 mm
Width	400 mm
Dimension a	201 mm
Dimension A	400 mm
Dimension b	253 mm
Dimension h	60 mm

Technical data sheet

Extension unit for GES6, height 60-110 mm

Item number: 7424902



Technical data			
	Mounting opening cover	yes	
	Covers	1	
	Number of mounting openings	1	
	Cover fastening, locking	no	
	Seal installation option	yes	
	Installation opening for on-floor tank	no	
	Installation opening for flush- mount unit	Rectangular	
	Decouplable	no	
	Suitable for expansion joint	no	
	Suitable for screed-flush closed underfloor ducts	no	
	Suitable for flushfloor, open un- derfloor trunking	yes	
	Suitable for screed-covered un- derfloor ducts	no	
	Trunking height, max.	110 mm	
	Duct height, min.	60 mm	
	Cover material thickness	4	
	Minimum screed height	60	
	With connection opening	yes	
	With equipotential bonding	no	
	With separating retainer	no	
	With overhang	yes	
	Mounting opening	For service outlet	
	Nominal size for device installati- on units	6	
	Height-adjustment range, max.	110 mm	
	Height-adjustment range, min.	60 mm	
	Removable cover	yes	