## **Technical data sheet**

0° socket, Switzerland, single

**Item number: 6117200** 



Socket, single  $0^{\circ}$ , to Swiss standard (SEV), with screwless terminals, 2-pin, 10 A, 250 V $^{\sim}$ , type 13, with connection terminals to IEC 60884-1. For installation in Rapid 45 ducts, device installation ducts, installation columns, underfloor systems and Deskboxes.



PC

Polycarbonate

| М   | _ | _ | 4. |    |     |     | 4- |
|-----|---|---|----|----|-----|-----|----|
| IVI | ы | S | Tf | 31 | . ( | 112 | па |

| Item number                           | 6117200                 |
|---------------------------------------|-------------------------|
| Description 1                         | Socket Swiss standard   |
| Manufacturer                          | OBO                     |
| Dimension                             | 250V, 10A               |
| Colour                                | Pure white; RAL 9010    |
| Material                              | Polycarbonate           |
| Smallest sales unit                   | 1                       |
| Unit of quantity                      | Piece                   |
| Weight                                | 3.4 kg                  |
| Weight unit                           | kg/100 pc.              |
| CO Footprint (GWP) Cradle-to-<br>Gate | 0,0185 kg COe / 1 Piece |

## **Technical data sheet**

## 0° socket, Switzerland, single

**Item number: 6117200** 





## Technical data

| Cover  | Central plate                |
|--|------------------------------|
| Closable   | no                           |
| Number of units                                  | 1                            |
| Printed label/coding                             | Without printing             |
| Version for                                      | Single 0°                    |
| Surface version                                  | Not applicable               |
| Version for                                      | Swiss Standard, Type 13      |
| Fastening type                                   | Lock                         |
| Labelling panel                                  | no                           |
| Operating temperature, max.                      | 40 °C                        |
| Operating temperature, min.                      | -5 °C                        |
| increased touch protection                       | no                           |
| Error current protection                         | no                           |
| For more difficult conditions (according to VDE) | no                           |
| Power reserve                                    | no                           |
| Halogen-free                                     | no                           |
| Hinged cover                                     | no                           |
| Warning light                                    | no                           |
| With on/off switch                               | no                           |
| With fine-wire fuse                              | no                           |
| With functional lighting                         | no                           |
| With orientation lighting                        | no                           |
| Mounting type                                    | Device installation duct     |
| Nominal voltage                                  | 250 V                        |
| Nominal current                                  | 10 A                         |
| Protection rating                                | Other                        |
| Special power supply                             | Without special power supply |
| Socket angle                                     | 0°                           |
| Depth  | 39.5 mm                      |
| Transparent                                      | no                           |
| Rotated central insert                           | no                           |
| Surge protection                                 | no                           |