Technical data sheet

Earth rod BP hot galvanised, 25 mm

Item number: 5000955



- "BP" system (Bundespost)
- Very good contacting properties with soft metal inlay in the bore hole
- With peg and bore for linking together
- FT version with zinc coating approx. 130 µm
- Conforms to the requirements according to VDE 0185-305 (IEC 62305) and DIN EN 62561-2

St Steel

FT Hot-dip galvanised

Master data


Item number	5000955
Type	219 25 BP FT
Description 1	Earth rod
Manufacturer	OBO
Dimension	1,5m
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	5
Unit of quantity	Piece
Weight	573 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	15,935 kg CO2e / 1 Piece

Technical data sheet

Earth rod BP hot galvanised, 25 mm

Item number: 5000955

Dimensions



Length	1,500 mm
Dimension L	1,500 mm

Technical data sheet

Earth rod BP hot galvanised, 25 mm

Item number: 5000955

Technical data

Version for	Miscellaneous
Design earth rod	BP
Lightning current carrying capacity	H/100 kA
Short-circuit current (50 HZ)(1 s; ≤300°C)	12.3 kA
Profile type	Round D=20 mm
ROHS-conformant	yes
Connection type	With pin/drill hole