Technical data sheet

Flat angle, asymmetrical, rising, for device installation trunking Rapid 80 type GS-A90130
Item number: 6277520

Flat angle, rising, for changing the direction of the GS device installation trunking.



St Steel


Master data

Item number	6277520
Type	GS-AFS90130RW
Description 1	Flat angle
Description 2	rising asymmetrical
Manufacturer	OBO
Dimension	90x130x300
Colour	Pure white; RAL 9010
Material	Steel
Smallest sales unit	1
Unit of quantity	Piece
Weight	152 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	5,8112 kg CO2e / 1 Piece

Technical data sheet

Flat angle, asymmetrical, rising, for device installation trunking Rapid 80 type GS-A90130
Item number: 6277520

Dimensions



Length	300 mm
Width	130 mm
Height	90 mm

Technical data

Number of covers	1
Version for	Base
for duct width	130 mm
for trunking height	90 mm
Halogen-free	yes
Cable retaining clip	no
Duct connector	no
Cover mounting type	Internal
Mounting perforation in base	yes
Cover width	76.5 mm
Change of direction	Vertical rising
Protection rating	IP30
Protective film	yes
Protection rating IK code	IK10
Symmetrical	no
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-25 °C
Angle range, min.	90 mm