Technical data sheet

Flat angle, symmetrical, falling, double, for device installation trunking Rapid 80 type GS-D70210
Item number: 6278430



Flat angle, falling, for changing the direction of the GS device installation trunking.

St Steel


Master data

Item number	6278430
Type	GS-DFF70210RW
Description 1	Flat angle
Description 2	falling symmetrical
Manufacturer	OBO
Dimension	70x210x300
Colour	Pure white; RAL 9010
Material	Steel
Smallest sales unit	1
Unit of quantity	Piece
Weight	177 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	11,7893 kg CO2e / 1 Piece

Technical data sheet

Flat angle, symmetrical, falling, double, for device installation trunking Rapid 80 type GS-D70210
Item number: 6278430

Dimensions



Length	300 mm
Width	210 mm
Height	70 mm

Technical data

Number of covers	2
Version for	Base
for duct width	210 mm
for trunking height	70 mm
Halogen-free	yes
Cable retaining clip	no
Duct connector	no
Cover mounting type	Internal
Mounting perforation in base	yes
Cover width	76.5 mm
Cover width 2	76.5 mm
Change of direction	Vertical, falling
Protection rating	IP30
Protective film	yes
Protection rating IK code	IK10
Symmetrical	no
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-25 °C
Angle range, min.	90 mm