# Technical data sheet

## Height-adjustable heavy-duty cassette, blank, RKNSL, nominal size 4, stainless steel
## Item number: 7408920



"Blank" height-adjustable cassette of nominal size 4 for the creation of an inspection opening. Installation in duct systems, raised and cavity floors in interior dry or wet-care floors. Load class 1 to 10 kN. Only suitable for smooth floor coverings.
For the installation of two UT3 universal supports for four single devices with support ring/support clamp or six Modul 45® devices. 2 APMT2 cover plates can be installed.

IP 55

A2 Stainless steel


### Master data


| | |
|---|---|
| Item number | 7408920 |
| Type | RKN3 4 V SL1 15 |
| Description 1 | Square cassette SL1 |
| Description 2 | blank lid |
| Manufacturer | OBO |
| Dimension | 199x199x100 |
| Material | Stainless steel |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 370 kg |
| Weight unit | kg/100 pc. |
| CO2 Footprint (GWP) Cradle-to-Gate | 16,2608 kg CO2e / 1 Piece |

# Technical data sheet

## Height-adjustable heavy-duty cassette, blank, RKNSL, nominal size 4, stainless steel
## Item number: 7408920

### Dimensions




| | |
|---|---|
| Length | 199 mm |
| Width | 199 mm |
| Height | 105 mm |
| Dimension h | 105 mm |

### Technical data

| | |
|---|---|
| Number of installable devices | 0 |
| Number of cable outlets | 0 |
| Number of universal supports | 2 x UT3 |
| Cover version | Square |
| Cable outlet version | No cable outlet |
| Floor cut-out / Mounting opening | 201x201 |
| Floor care | Wet |
| Decouplable | no |
| Floor height, max. | 150 mm |
| Floor height, min. | 105 mm |
| Suitable for raised floor installation | yes |
| Suitable for cavity floor installation | yes |
| Suitable for underfloor box | 250/350 |
| Device support to accept mounting boxes | no |
| Length of installation dimensions | 201 mm |
| Nominal size for device installation units | 4 |
| Height-adjustment range, max. | 150 mm |
| Height-adjustment range, min. | 105 mm |
| Standard | EN 50085-2-2 |
| ROHS-conformant | Exempt |
| Protection rating (IP) when used | IP00 |
| Protection rating (IP) when unused | IP55 |
| Protection rating IK code | IK10 |
| Heavy-duty version | yes |
| Heavy load class | 10 kN (OBO SL1) |
| Installation system type | UT3 |
| Approvals | VDE |
| Floor covering thickness | 15 mm |